

GRIP TUBE Easy stop & Multi wire diameter sleeve



Specially designed internal shape helps your markers hold a fixed position on the wire, even when using multiple wire diameter sizes. This material is a good fit to ferrule terminals.

* Attachment for small diameter tube in the printer hard case should be applied to the appropriate place as below photo.

*(Vinyl(PVC)/Drum roll/Not UL certified)

Туре	Specification	
LM-TU29G WHITE	ϕ 1.9 \sim 2.1mm x 100m(109.4y)/ROLL	
LM-TU37G WHITE	ϕ 2.5 \sim 2.7mm x 100m(109.4y)/ROLL	









set as above









easy move



easy stop

Tube (Vinyl (PVC) / Drum roll / Not UL certified)

MAX has made the Drum Type Roll our quality standard for tube marking. The drum roll box design allows the tube to feed smoothly and automatically into the printer, making it possible for workers to print large batches without constantly watching the machine.



	20020
Туре	Specification
LM-TU425L2 WHITE	φ2.5mm X 250m(273.4y)/ROLL
LM-TU427L2 WHITE	φ2.7mm X 250m(273.4y)/ROLL
LM-TU432L2 WHITE	φ3.2mm X 250m(273.4y)/ROLL
LM-TU434L2 WHITE	φ3.4mm X 250m(273.4y)/ROLL
LM-TU436L2 WHITE	φ3.6mm X 250m(273.4y)/ROLL
LM-TU442L WHITE	φ4.2mm X 200m(218.7y)/ROLL
LM-TU452L WHITE	φ5.2mm X 135m(147.6y)/ROLL
LM-TU464L WHITE	φ6.4mm X 100m(109.4y)/ROLL
LM-TU480L WHITE	φ8.0mm X 70m(76.6y)/ROLL

N Tube (UL224/E171616/105°C/600V)

The 'N' tube series has acquired the UL224 certification, and provides high insulation performance for sites with this requirement.



Type	Specification	
LM-TU332N2 WHITE	φ3.2mm X 100m(109.4y)/ROLL	
LM-TU336N2 WHITE	φ3.6mm X 100m(109.4y)/ROLL	
LM-TU342N2 WHITE	φ4.2mm X 80m(87.5y)/ROLL	
LM-TU352N2 WHITE	φ5.2mm X 80m(87.5y)/ROLL	

White plate for transparent sleeves, you can print letters on it and half cut with LETATWIN printers.







*Expression of `Halogen Free` is accordance with IEC 61249-2-21 , Chlorine (CI) \leq 0.09wt% (900ppm), Bromine (Br) \leq 0.09wt% (900ppm), total content rate of both materials is \leq 0.15wt% (1500ppm).

Polyester Tapes (Width 5mm/9mm/12mm/White/Yellow/Transparent)






Туре	Specification	
LM-TP505W (WHITE)	5mm(W) X 16m(17.5y)(L)/PC	
LM-TP505Y (YELLOW)	5mm(W) X 8m(8.7y)(L)/PC	
LM-TP505T (TRANSPARENT)	5mm(W) X 8m(8.7y)(L)/PC	
LM-TP509W (WHITE)	9mm(W) X 16m(17.5y)(L)/PC	
LM-TP509Y (YELLOW)	9mm(W) X 8m(8.7y)(L)/PC	
LM-TP509T (TRANSPARENT)	9mm(W) X 8m(8.7y)(L)/PC	
LM-TP512W (WHITE)	12mm(W) X 16m(17.5y)(L)/PC	
LM-TP512Y (YELLOW)	12mm(W) X 8m(8.7y)(L)/PC	

Markable Slide Plate w10.7 x t0.5mm for Terminal block marking



Stick printed tape onto Slide Plate



Insert Slide Plate into Teminal Block



Other items







^{*}The specifications and design of products in this catalog will be subject to change without advance notice of our products due to our continuous efforts to improve quality.

Ink Ribbons for Heat Shrink/Vinyl (PVC) Tube and Polyester Tape





Heat Shrink Tubing / ID Plate



BLACK Ink Ribbon







Economical Re-fill Type Ink Ribbon

*Expression of `Halogen Free` is accordance with IEC 61249-2-21, Chlorine (Cl) \leq 0.09wt% (900ppm), Bromine (Br) \leq 0.09wt% (900ppm), total content rate of both materials is ≤ 0.15 wt% (1500ppm).

How it works

LM-IR50B (Green Core)



Check the outer wire diameter.

USA	Recommended Tube Size			
Wire	GRIP	N2	L2 and L	
AMG24	TU29G	-	-	
AMG22	TU37G	-	TU425	
AMG20		-	TU425	
AMG18		-	TU427	
AMG16	-	TU332	TU432	
AMG14	-	TU336	TU434 or 436	
AMG12	-	TU342	TU442	
AMG10	-	TU352	TU452	
AMG8	-	-	TU464	
AMG6	-	-	TU480	

Select appropriate tubing size.



Set the tubing on LETATWIN.



LETATWIN prints and half cut the tubing.

The specification and design of products in this catalog will be subject to change without advance notice due to our continuous efforts to improve quality.

Insert 2pcs of the marked blocks



MAX USA CORP.

205 Express Street, Plainview, NY 11803 Phone: (516)741-3151 Fax: (516)741-3272 WWW.MAXUSACORP.COM/SIGN_MARKING



Lim Kim Hai Electric Co (S) Pte Ltd Lim Kim Hai Building,

53 Kallang Place, Singapore 339177

(+65) 6292 3711 • (+65) 6490 5000

(+65) 6297 0078

customerservice@limkimhai.com.sg W www.limkimhai.com.sq